

REDUCE YOUR PULL TIME!

Houston Wire & Cable Company (HWC) provides pulling-eye products and installation services. Increase productivity, lower costs and save time at the job site by receiving your wire and cable with installed pulling eyes.

Installation Services:

- + Quick turnaround
- + Cut to length
- + Installed and delivered - ready to pull

Pulling Eye Features:

- + Available for cable sizes 8AWG - 1000MCM
- + Single use lugs and lanyards
- + Low-profile pulling head
- + Parallel up to 5 conductors
- + Crimps to conductor, not jacket
- + Rated for both copper and aluminum
- + Beveled edge for easier pulls around corners

Job Site Benefits:

- + Reduces on-site labor costs
- + Reduces total pull hardware
- + Pull four times as much wire per day
- + Reduce set-up & installation times, wire arrives ready to pull
- + Easy to pull multiple or single lugs
- + Small pulling heads reduce friction and eliminate oversize conduit
- + More secure than grips



**PULLING EYES
ARE
AVAILABLE
FOR STOCK OR
PRE-INSTALLED
BY A CERTIFIED
HWC INSTALLER**



Ideal for most single conductor 8AWG & larger cables:

- + 600V through 35kV rated wire
- + Aluminum & Copper Cables
- + THHN
- + XHHW
- + RHW/RHH/USE



Single-Use Pulling Eye Lanyard Length Options

Cable Size (AWG)	Lanyard Lengths (in.)
1/0 – 750	14", 21", 28", 35"
8 – 1	11", 15", 19", 23"

Single-Use Pulling Eye Part # Reference

The lanyards are available in a variety of lengths to make staggering multiple wire pulls effortless, especially through and around nineties.

HWC Part #	Description	Ultimate Holding Value
1000-14PE	1000MCM/14" LANYARD	5500 lb
1000-21PE	1000MCM/21" LANYARD	5500 lb
1000-28PE	1000MCM/28" LANYARD	5500 lb
1000-35PE	1000MCM/35" LANYARD	5500 lb
750-14PE	750MCM/14" LANYARD	5500 lb
750-21PE	750MCM/21" LANYARD	5500 lb
750-28PE	750MCM/28" LANYARD	5500 lb
750-35PE	750MCM/35" LANYARD	5500 lb
600-14PE	600MCM/14" LANYARD	5500 lb
600-21PE	600MCM/21" LANYARD	5500 lb
600-28PE	600MCM/28" LANYARD	5500 lb
600-35PE	600MCM/35" LANYARD	5500 lb
500-14PE	500MCM/14" LANYARD	5000 lb
500-21PE	500MCM/21" LANYARD	5000 lb
500-28PE	500MCM/28" LANYARD	5000 lb
500-35PE	500MCM/35" LANYARD	5000 lb
400-14PE	400MCM/14" LANYARD	4500 lb
400-21PE	400MCM/21" LANYARD	4500 lb
400-28PE	400MCM/28" LANYARD	4500 lb
400-35PE	400MCM/35" LANYARD	4500 lb
350-14PE	350MCM/14" LANYARD	4000 lb
350-21PE	350MCM/21" LANYARD	4000 lb
350-28PE	350MCM/28" LANYARD	4000 lb
350-35PE	350MCM/35" LANYARD	4000 lb
300-14PE	300MCM/14" LANYARD	3000 lb
300-21PE	300MCM/21" LANYARD	3000 lb
300-28PE	300MCM/28" LANYARD	3000 lb
300-35PE	300MCM/35" LANYARD	3000 lb
250-14PE	250MCM/14" LANYARD	2000 lb
250-21PE	250MCM/21" LANYARD	2000 lb
250-28PE	250MCM/28" LANYARD	2000 lb
250-35PE	250MCM/35" LANYARD	2000 lb
4/0-14PE	4/0AWG/14" LANYARD	1700 lb
4/0-21PE	4/0AWG/21" LANYARD	1700 lb
4/0-28PE	4/0AWG/28" LANYARD	1700 lb
4/0-35PE	4/0AWG/35" LANYARD	1700 lb

HWC Part #	Description	Ultimate Holding Value
3/0-14PE	3/0AWG/14" LANYARD	1500 lb
3/0-21PE	3/0AWG/21" LANYARD	1500 lb
3/0-28PE	3/0AWG/28" LANYARD	1500 lb
3/0-35PE	3/0AWG/35" LANYARD	1500 lb
2/0-14PE	2/0AWG/14" LANYARD	1100 lb
2/0-21PE	2/0AWG/21" LANYARD	1100 lb
2/0-28PE	2/0AWG/28" LANYARD	1100 lb
2/0-35PE	2/0AWG/35" LANYARD	1100 lb
1/0-14PE	1/0AWG/14" LANYARD	1100 lb
1/0-21PE	1/0AWG/21" LANYARD	1100 lb
1/0-28PE	1/0AWG/28" LANYARD	1100 lb
1/0-35PE	1/0AWG/35" LANYARD	1100 lb
1-11PE	1AWG W/11" LANYARD	1000 lb
1-15PE	1AWG W/15" LANYARD	1000 lb
1-19PE	1AWG W/19" LANYARD	1000 lb
1-23PE	1AWG W/23" LANYARD	1000 lb
2-11PE	2AWG W/11" LANYARD	600 lb
2-15PE	2AWG W/15" LANYARD	600 lb
2-19PE	2AWG W/19" LANYARD	600 lb
2-23PE	2AWG W/23" LANYARD	600 lb
3-11PE	3AWG W/11" LANYARD	500 lb
3-15PE	3AWG W/15" LANYARD	500 lb
3-19PE	3AWG W/19" LANYARD	500 lb
3-23PE	3AWG W/23" LANYARD	500 lb
4-11PE	4AWG W/11" LANYARD	350 lb
4-15PE	4AWG W/15" LANYARD	350 lb
4-19PE	4AWG W/19" LANYARD	350 lb
4-23PE	4AWG W/23" LANYARD	350 lb
6-11PE	6AWG W/11" LANYARD	300 lb
6-15PE	6AWG W/15" LANYARD	300 lb
6-19PE	6AWG W/19" LANYARD	300 lb
6-23PE	6AWG W/23" LANYARD	300 lb
8-11PE	8AWG W/11" LANYARD	200 lb
8-15PE	8AWG W/15" LANYARD	200 lb
8-19PE	8AWG W/19" LANYARD	200 lb
8-23PE	8AWG W/23" LANYARD	200 lb